

H G F E D C B A



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

CHARACTERISTICS

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Composite
- Shell Plating : Without Plating
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered without Souriau contacts
- Temperature Range : -65°C to +175°C
- Salt Spray : 2000 hours

| Connector dimension | |
|---------------------|----------|
| Dim | Nominal |
| ØS | 41.7 Max |
| Z | 31 Max |
| VV THREAD | M31x1-6g |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR | Not Listed |

PN: 8D521X77PCL

| | | | |
|---------------------|------------|--|-------------------------------|
| A | 11-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | | Composite Plug 8D series | |
| SCALE | NA | General linear Tolerances: ±-- | NPRDS / PROJECT 859 |
| SOURIAU | | WWW.SOURIAU.COM | |
| FORMAT A3 | | SOURIAU DRG N° 8D521X77PCL-C | |
| | | | SHEET 1/2 |

| | | | | | | | | | | |
|----------------|-------------------------|---|---|----|---------------------------------|----|---|---|---|------------------------|
| BASIC SERIES: | 8D | 5 | - | 21 | X | 77 | P | C | L | Delivered W/O Contacts |
| SHELL TYPE : | Plug with RFI Shielding | | | | ORIENTATION : C | | | | | |
| CONTACT TYPE : | Standard Crimp Contact | | | | CONTACT TYPE : PIN(500 Matings) | | | | | |
| SHELL SIZE : | 21 | | | | CONTACT LAYOUT : 21-77 | | | | | |
| PLATING : | X = Without Plating | | | | | | | | | |

4

3

2

1

H G F E D C B A

Contact Layout

77



17#22D
2#8 Triax

| 21-77 | | |
|-------|--------|-------|
| Ctc | X | Y |
| A | 1.96 | 8.38 |
| B | 5.46 | 7.67 |
| C | 8.51 | 5.79 |
| D | 10.46 | 2.82 |
| E | 10.46 | -2.82 |
| F | 8.51 | -5.79 |
| G | 5.46 | -7.67 |
| H | 1.96 | -8.38 |
| J | 0 | -5.41 |
| K | -1.96 | -8.38 |
| L | -5.46 | -7.67 |
| M | -8.51 | -5.79 |
| N | -10.46 | -2.82 |
| P | -10.46 | 2.82 |
| R | -8.51 | 5.79 |
| S | -5.46 | 7.67 |
| T | -1.96 | 8.38 |
| U | -4.57 | 0 |
| V | 4.57 | 0 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| | |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR | Not Listed |

PN: 8D521X77PCL

| | | | |
|----------------|-------------------------------------|----------------------------|---|
| A | 11-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | Composite Plug 8D series | | |
| SCALE | | General linear Tolerances: | NPRDS / PROJECT |
| NA | | ±-- | 859 |
| SOURIAU | WWW.SOURIAU.COM | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT | SOURIAU DRG N° 8D521X77PCL-C | | SHEET 2/2 |