

GWX-2012

2012 Package 32.768kHz Watch Crystal

- Competitive pricing for volume applications
- Ultra low profile - 0.6mm high
- Light weight miniature package
- Vacuum sealed for high stability






CONFIGURABLE OPTIONS

Parameter	Option Code
Calibration tolerance	
±20ppm	
Circuit condition	
Any	
6pF	
7pF	
9pF	
12.5pF	


SPECIFICATIONS

Frequency	32.768kHz
Dimensions	2.05 x 1.2 x 0.6mm
Operating temperature range	-40 to +85°C
Storage temperature range	-55 to +125°C
Static capacitance (C ₀)	1.3pF typ
Equivalent series resistance	70kΩ max @ 25°C
Ageing	±3ppm max first year
Drive level	1.0μW max
Turnover temperature (T ₀)	+25°C ±5°C
Frequency / temp coefficient	-0.033ppm/°C ² typ
Net mass	4.6mg

PACKAGE DRAWING



SOLDER PAD LAYOUT



TOP VIEW

Dimensions in mm


ORDERING INFORMATION

To request a quotation for the GWX-2012 please use the configurable options form to choose the options you require and then submit your configured product to our team. Our expert advisers are always happy to help with your requirements and can be contacted on +44 1460 256 100 or at sales@golledge.com.


Following product selection you will be issued with a seven character Golledge part number. Your Golledge part number is the internationally accepted Golledge manufacturing part number (MPN) that should be used for all project documentation, including bills of materials (BoMs) and purchase orders.

If you have any queries regarding any of our documentation our dedicated sales team will be happy to help.

SOLDERING PROFILE



TAPE & REEL SPECIFICATION



Dimensions in mm

HANDLING & STORAGE



Human Body Model (HBM) 1A (250V to <500V)




Moisture Sensitivity Level (MSL): 1 (or not applicable)


CONSTRUCTION

Ceramic body with gold-plated pads
Metal lid, vacuum sealed


COMPLIANCE


Please refer to our **DOCUMENTS** section for more information.


 Lead-free (< 0.1% by weight)

 RoHS compliant with no exemptions.

 REACH compliant.

 Free of conflict minerals.

 Free from halogens.

 Free from ozone-depleting substances.